

# PATENT COOPERATION TREATY

# PCT

## INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference <b>MM/00007/PCT</b>	<b>FOR FURTHER ACTION</b> see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. <b>PCT/EP 01/ 00815</b>	International filing date (day/month/year) <b>24/01/2001</b>	(Earliest) Priority Date (day/month/year) <b>25/01/2000</b>
Applicant  <b>PIRELLI PNEUMATICI S.P.A.</b>		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

This International Search Report consists of a total of 2 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

**1. Basis of the report**

a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established by this Authority to read as follows:

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

1 \_\_\_\_\_  
☐ None of the figures.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
2 August 2001 (02.08.2001)

PCT

(10) International Publication Number  
**WO 01/54955 A1**

- (51) International Patent Classification<sup>7</sup>: **B60T 8/00**
- (21) International Application Number: PCT/EP01/00815
- (22) International Filing Date: 24 January 2001 (24.01.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
00830041.0 25 January 2000 (25.01.2000) EP  
60/199,385 25 April 2000 (25.04.2000) US
- (71) Applicant (for all designated States except US): **PIRELLI PNEUMATICI S.P.A.** [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MANCOSU, Federico** [IT/IT]; Via Antonio Dossi, 6, I-20135 Milano (IT). **MATRASCIA, Giuseppe** [IT/IT]; Via Valassina, 14, I-20038 Seregno (IT).
- (74) Agents: **MARCHI, Massimo**; Via Pirelli, 19, I-20124 Milano et al. (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DEVICE FOR CONTINUOUSLY MEASURING DEFORMATIONS IN A TYRE DURING THE TRAVEL MOVEMENT OF A MOTOR VEHICLE



(57) Abstract: A device (20) for continuously measuring deformations in a tyre (1), which is mounted on a rim (5), comprises at least one first emitter (7) of a first direct light beam (8), at least one first optical sensor (9) of the luminous intensity and at least one first reflecting element (13, 113) applied to a first portion (21) of an inner surface (4) of the tyre (1); the first emitter (7) is mounted on the rim (5) and is capable of sending the first direct light beam (8) towards the first reflecting element (13, 113); the first optical sensor (9) is also mounted on the rim (5) and is capable of receiving a first reflected light beam from the first reflecting element (13, 113), measuring a first prechosen physical parameter associated with the first reflected light beam and providing a first signal representing the deformation affecting the tyre (1) along the first surface portion (21) during one revolution of the tyre (1).

WO 01/54955 A1

- 1 -

"Device for continuously measuring deformations in a tyre during the travel movement of a motor vehicle "

\*\*\*\*\*

5 The present invention relates to a device for continuously measuring deformations in a tyre during the travel movement of a motor vehicle.

During the travel movement of a motor vehicle, if the operating conditions of a tyre are known, it is possible to perform operations for controlling and adjusting the behaviour of the motor vehicle. In particular, it is useful to know whether there is skidding or no skidding of the tyre, the variation in the amount of grip available compared to a reference condition, the variation in the forces exchanged between tyre and road, so as to activate, for example, devices for preventing locking during braking (anti-skid or ABS devices), devices for preventing skidding during acceleration, active suspension systems, etc.

15 A device for controlling the behaviour of the tyre is described in European patent application No. 99830714.4 filed on 18 November 1999 in the name of the same Applicants.

20 This device comprises one or more sensors which are situated at prechosen points on a tyre during its rolling travel and are capable of emitting signals indicating the spatial position assumed by these points. The signals for the position of a point on the tyre are used to determine the cyclical displacement thereof, namely the displacement pattern of the point during each revolution of the tyre, and from the latter the cyclical pattern of the speed is determined. Depending on the situation to be controlled, the longitudinal displacement (direction of forward travel of the tyre), transverse or lateral displacement (perpendicular to the direction of forward

25

- 2 -

travel), vertical displacement of the point and the associated speed are taken into consideration.

5 The device performs a comparison between the cyclical pattern of the speed of the point detected during the i-th revolution and a cyclical pattern of a reference speed, in particular that detected during the i-th-1 revolution, i.e. immediately beforehand, and provides a signal indicating the instantaneous behaviour of the tyre. The sensors used in this device are associated with the tyre. It has now been found that it is possible to obtain even better results using a device comprising at least one sensor located on a rim on which the tyre is mounted.

15 A first aspect of the invention relates to a device for continuously measuring deformations in a tyre, which is mounted on a rim, during the travel movement of a motor vehicle, characterized in that it comprises at least one first emitter of a first direct light beam, at least one first optical sensor of the luminous intensity and at least one first reflecting element applied to a first portion of an inner surface of said tyre, said first emitter being mounted on said rim and being capable of sending said first direct light beam towards said first reflecting element, said first optical sensor also being mounted on said rim and being capable of receiving a first reflected light beam from said first reflecting element, measuring a first prechosen physical parameter associated with said first reflected light beam and providing a signal representing the deformation affecting said tyre along said first surface portion during one revolution of said tyre.

20 Advantageously, said first prechosen physical parameter consists of the luminous intensity of said first reflected light beam.

Preferably, said device also comprises a second emitter of a second direct light beam, a second optical sensor of the luminous intensity and a second reflecting element applied to a second portion

- 3 -

of the said inner surface of said tyre, situated in the vicinity of said first surface portion, said second emitter being mounted on said rim and being capable of sending said second direct light beam towards said second reflecting element, said second optical sensor also  
5 being mounted on said rim and being capable of receiving a second reflected light beam from said second reflecting element, measuring a second prechosen physical parameter associated with said second reflected light beam and providing a signal representing the variation in distance which has occurred between said second surface portion  
10 and said rim during one revolution of said tyre.

According to one embodiment, said second prechosen physical parameter consists of the luminous intensity of said second reflected light beam.

According to a variant, said second prechosen physical parameter  
15 consists of the time which lapses between sending of said second direct light beam and receiving of said second reflected light beam, said second direct light beam having a given wavelength.

Advantageously, said first and second optical sensors are operationally connected to processor means capable of determining,  
20 by means of said deformation signal, a signal representing the displacement of at least one point on said first surface portion in a predetermined direction, correcting said displacement signal depending on said variation-in-distance signal and providing an output signal for displacement of said at least one point in said  
25 predetermined direction, independent of said variation in distance. Preferably, said processor means are capable of providing, by means of said variation-in-distance signal, a measurement of the vertical compression of said tyre.

A second aspect of the invention relates to a motor vehicle wheel,  
30 comprising a tyre mounted on a rim, characterized in that it

- 4 -

comprises, in turn, a device for continuously measuring deformations in said tyre during the travel movement of said motor vehicle, said device comprising at least one first emitter of a first direct light beam, at least one first optical sensor of the luminous intensity and at least one first reflecting element applied to a first portion of an inner surface of said tyre, said first emitter being mounted on said rim and being capable of sending said first direct light beam towards said first reflecting element, said first optical sensor also being mounted on said rim and being capable of receiving a first reflected light beam from said first reflecting element, measuring a first prechosen physical parameter associated with said first reflected light beam and providing a first signal representing the deformation affecting said tyre along said first surface portion during one revolution of said tyre.

Preferably, said device of said wheel also comprises a second emitter of a second direct light beam, a second optical sensor of the luminous intensity and a second reflecting element applied to a second portion of said inner surface of said tyre, situated in the vicinity of said first surface portion, said second emitter being mounted on said rim and being capable of sending said second light beam towards said second reflecting element, said second optical sensor also being mounted on said rim and being capable of receiving a second reflected light beam from said second reflecting element, measuring a second prechosen physical parameter associated with said second reflected light beam and providing a second signal representing the variation in distance which has occurred between said second surface portion and said rim during one revolution of said tyre.

The device according to the invention has the advantage that it is safe and reliable.

- 5 -

Characteristic features and advantages of the invention will now be described with reference to an embodiment shown by way of a non-limiting example in the accompanying figures in which:

Fig. 1 is a cross-sectional view of a device for continuously measuring deformations in a tyre for a motor vehicle, constructed in accordance with the invention;

Fig. 2 is a front view of a reflecting element applied to an inner surface of the tyre according to Fig. 1 and a light spot associated therewith;

Fig. 3 shows the reflecting element according to Fig. 2 in the undeformed and deformed condition;

Fig. 4 shows a variant of the reflecting element according to Fig. 2;

Fig. 5 shows a variant of the device according to Fig. 1;

Figs. 6, 7, 8 and 9 are graphs which show the pattern of displacements affecting a point on the surface portion of the tyre according to Fig. 1, to which the reflecting element according to Fig. 2 is applied.

Fig. 1 shows a tyre 1 for a motor vehicle, having a carcass 2 and a tread 3. The carcass 2 has, applied to it, a liner 6 which has an inner surface 4. The tyre 1 is mounted on a rim 5. The tyre 1 has, associated with it, a device 20 for measuring deformations, comprising an emitter 7 of a direct light beam 8 and an optical sensor 9 of the luminous intensity. The emitter 7 and the sensor 9 are fixed to the rim 5 and are operationally connected to the tyre 1.

A reflecting element 13, which is for example white-coloured and in the form of an arrow (Fig. 2) or a rectangular strip 113 (Fig. 4) or a small disk, is applied onto a portion 21 of the inner surface 4 of the tyre 1, which is normally black-coloured. The reflecting element 13 is obtained, for example, by means of colouring using colouring materials having an elastic modulus similar to that of the liner 6 so

- 6 -

as to prevent the occurrence of surface tension which could falsify the results of the measurements.

5 The emitter 7 and the sensor 9 are located opposite the reflecting element 13. This relative position is maintained in any rolling condition of the tyre and at any speed.

10 The emitter 7 emits a light beam 8 of known intensity which strikes the reflecting element 13. The optical sensor 9 measures the luminous intensity of the light beam reflected by the reflecting element 13 and emits a signal (radio waves) which is transmitted remotely to a processor, represented by a block 15. The luminous intensity of the reflected light beam may be associated with a wavelength, namely with a colour or with a wavelength band. In the first case, the sensor 9 is of the photochromatic type and the reflecting element 13 has a colour different from that of the liner. In the second case, the reflecting element 13 has a reflecting capacity which is greater than that of the surface 4.

15 The sensor 9 has a well-defined spot 16 (Fig. 2). "Spot" is understood as meaning the area of the surface 4 over which the sensor is able to perform its analysis. The spot has an area lying in a range of from 15 mm<sup>2</sup> to 1600 mm<sup>2</sup>. The reflecting element 13 is positioned in the spot zone and the sensor 9 emits a signal proportional to the ratio between the reflecting element 13 and the total area of the spot 16.

20 In other words, the sensor 9 is able to analyse the colour situation on the spot surface and detect which proportion is black and which proportion consists of the colour prechosen for the reflecting element 13, for example white.

25 In the case where the spot has an area of 100 mm<sup>2</sup> and if the white surface area of the reflecting element is equal to 35 mm<sup>2</sup>, the sensor 9 emits a proportional analog signal 35/100ths of its scale

30



- 7 -

limit value. If the scale limit value is 10 Volts (equivalent to a 100% white area with no black), the sensor emits a signal of 3.5 Volts.

5 The intensity of the reflected beam measured by the sensor 9 depends on the deformation of the surface portion 4 to which the reflecting element 13 is applied.

10 During each revolution of the tyre 1, the surface portion 4 on which the reflecting element 13 is located comes into contact with the ground and is compressed. The reflecting element 13 is deformed and its arrow or rectangular strip shape is cyclically modified, becoming broader or smaller, depending on the stress and deformation condition of the surface portion 4 lying within the spot 16 and located opposite the sensor 9. Fig. 3 shows the deformation 13a of the arrow-shaped reflecting element 13 when the tyre 1 is in a braking condition.

15 During rolling of the tyre, the ratio between the area of the black part and the area of the reflecting part (white) is modified in the surface portion 4 lying within the spot 16 of the sensor 9. This variation in the white/black ratio is detected by the optical sensor 9 which emits a signal which is variable over time. The cyclical signal of the white/black ratio is calculated in the processor 15 and, from this signal, on the basis of the known dimensions of the arrow or the rectangular strip of the reflecting element 13, another cyclical signal is obtained, said signal representing the pattern, over time, of the longitudinal and transverse (lateral) displacement of a point or of prechosen points forming part of the area of the reflecting element 13 which is cyclically deformed.

25 Fig. 5 shows a device 120 which is a variant of the device 20 shown in Fig. 1 and identical parts are indicated by the same numbers.

- 8 -

The device 120 comprises, in addition to the emitter 7 and the sensor 9, an emitter 10 of a light beam 11 and an optical sensor 12. The sensor 12 may be either of the type able to measure the luminous intensity or of the type able to measure the time lapsing  
5 between emission and reception of the light beam, at a given wavelength of the emitted beam. The emitter 10 and the sensor 12 are also fixed to the rim 5 and are operationally connected to the tyre 1.

A portion 22 of the inner surface 4 of the tyre 1 has, applied to it,  
10 a reflecting element 14 having an ellipsoidal shape or any other suitable shape. The reflecting element 14 has a structure similar to that of the reflecting element 13. The emitter 10 and the sensor 12 are located opposite the reflecting element 14. This relative position is maintained in any rolling condition of the tyre and at any speed.

15 The sensor 12, in the same way as the sensor 9, emits a signal (radio waves) which is transmitted remotely to the processor 15. The emitters 7 and 10 emit light beams 8 and 11, respectively, which are of known intensity and wavelength and which strike the reflecting element 13 and the reflecting element 14, respectively. The optical  
20 sensor 9 measures the luminous intensity of the reflected light beam, while the sensor 12 is able to measure either luminous intensity of the reflected light beam or the time lapsing between emission and reception of the light beam on the basis of the known wavelength. In this way, the sensor 12 measures the vertical distance present  
25 between reflecting element 14 and rim 5. In fact, when this distance varies, the inclination of the transmitted light beam and therefore the intensity of the reflected light beam received by the sensor 12 changes.

30 In the device 120, the longitudinal and transverse displacement signals measured by the sensor 9 are corrected by means of the

- 9 -

signals emitted by the sensor 12 so as to take account of the fact that the dimensions of the spot analysed by the sensor 9 vary cyclically with the distance from the rim 5 owing to the compression which the tyre undergoes when entering into the area of contact with the ground and then leaving it. The distance varies between a value equal to the free radius of inflation and a value equal to the smaller free radius of compression.

The sensor 12 measures the intensity of the light beam reflected by the reflecting element 14, which varies depending on the distance travelled, and emits a signal representing the variation in distance. Alternatively, the sensor 12 measures the time lapsing between emission and reception and, on the basis of the known wavelength of the light beam, determines the variation in distance. The processor 15 uses the signal in order to update automatically and continuously the calibration setting of the sensor 9 and to determine the dimensions of the spot of the sensor 9, taking into account the variations in the abovementioned distance.

As a result, it is possible to obtain a correct measurement of the longitudinal and transverse displacements of the points considered on the surface 4, irrespective of the variation in the abovementioned distance.

In the case where the sensor 9 emits a signal which is not influenced by the variation in distance between reflecting element and rim, it is advantageous to use the device 20 shown in Fig. 1. Figs. 6, 7, 8 and 9 show the results obtained with the device according to the invention on a tyre of size 195/65 R15 and having an inflation pressure of 2 bar, a vertical load of 150 kg and a speed of 30 km/h.

- 10 -

Fig. 6 shows the pattern of the longitudinal displacements (mm), over time (sec), of a point on the liner, during free rolling conditions, in the zone of contact with the ground.

5 Fig. 7 shows the pattern of the longitudinal displacements (mm), over time (sec), of a point on the liner, during braking conditions, in the zone of contact with the ground. The braking manoeuvre was performed with a longitudinal force of 280 kg and skidding slip of 10%.

10 Fig. 8 shows the pattern of the lateral displacements (mm), over time (sec), of a point on the liner, during free rolling conditions, in the zone of contact with the ground, with a slip angle of 6 degrees.

Fig. 9 shows the pattern of the lateral displacements (mm), over time (sec), of a point on the liner, during free rolling conditions, with a slip angle of 0 degrees.

15 The signal for the variation in distance is also used in the processor 15 to provide a measurement of the vertical compression of the tyre. By monitoring the four tyres of the motor vehicle it is possible to determine the type of manoeuvre in progress.  
The vertical compression of the tyres which are situated on the right-  
20 hand side or on the left-hand side of the motor vehicle provides information as to the type of bend, i.e. a right-hand or left-hand bend, which the vehicle is negotiating.

25 When the vehicle is travelling around a left-hand bend, a transfer of load takes place from the wheels situated on the left-hand side (on the inside of the bend) to the wheels situated on the right-hand side (on the outside of the bend). The tyres situated on the right-hand side tend to be compressed more, compared to travel in a straight line, while the left-hand tyres tend to be compressed less. Similarly, during braking, there is a transfer of load from the rear  
30 wheels to the front wheels. The vertical compression of the front

- 11 -

tyres increases, compared to travel in a straight line. Conversely, during acceleration, the front wheels tend to be relieved of the load while the rear wheels are subject to a greater load. Therefore, the vertical compression of the rear tyres increases compared to travel in a straight line.

5           The processor 15, by means of the abovementioned measurement of the variation in distance, determines the current vertical compression of the four tyres of the motor vehicle and compares it with the compression detected during travel in a straight  
10 line and when no manoeuvres are performed, so as to provide information as to the type of bend or the type of manoeuvre in progress.

- 12 -

## CLAIMS

1. Device (20; 120) for continuously measuring deformations in a tyre (1), which is mounted on a rim (5), during the travel movement of a motor vehicle, characterized in that it comprises at least one first emitter (7) of a first direct light beam (8), at least one first optical sensor (9) of the luminous intensity and at least one first reflecting element (13; 113) applied to a first portion (21) of an inner surface (4) of said tyre (1), said first emitter (7) being mounted on said rim (5) and being capable of sending said first direct light beam (8) towards said first reflecting element (13; 113), said first optical sensor (9) also being mounted on said rim (5) and being capable of receiving a first reflected light beam from said first reflecting element (13; 113), measuring a first prechosen physical parameter associated with said first reflected light beam and providing a signal representing the deformation affecting said tyre (1) along said first surface portion (21) during one revolution of said tyre (1).
2. Device (20; 120) according to Claim 1, characterized in that said first prechosen physical parameter consists of the luminous intensity of said first reflected light beam.
3. Device (20; 120) according to Claim 1, characterized in that it also comprises a second emitter (10) of a second direct light beam (11), a second optical sensor of the luminous intensity (12) and a second reflecting element (14) applied to a second portion (22) of said inner surface (4) of said tyre (1), situated in the vicinity of said first surface portion (21), said second emitter (10) being mounted on said rim (5) and being capable of sending said direct light beam (11) towards said second reflecting element (14), said second optical sensor (12) also being mounted on said rim (5) and being capable of receiving a second reflected light beam from said second reflecting element (14), measuring a second prechosen physical parameter associated

- 13 -

with said second reflected light beam and providing a signal representing the variation in distance which has occurred between said second surface portion (22) and said rim (5) during one revolution of said tyre (1).

- 5 4. Device (20; 120) according to Claim 3, characterized in that said second prechosen physical parameter consists of the luminous intensity of said second reflected light beam.
5. Device (20; 120) according to Claim 3, characterized in that said second prechosen physical parameter consists of the time which  
10 lapses between sending of said second direct light beam (11) and receiving of said second reflected light beam, said second direct light beam (11) having a given wavelength.
6. Device (20; 120) according to Claims 1 and 3, characterized in that said first and second optical sensors (9, 12) are operationally  
15 connected to processor means (15) capable of determining, by means of said deformation signal, a signal representing the displacement of at least one point on said first surface portion (21) in a predetermined direction, correcting said displacement signal depending on said variation-in-distance signal and providing an  
20 output signal for displacement of said at least one point in said predetermined direction, independent of said variation in distance.
7. Device (20; 120) according to Claim 6, characterized in that said processor means (15) are capable of providing, by means of said variation-in-distance signal, a measurement of the vertical  
25 compression of said tyre (1).
8. Motor vehicle wheel comprising a tyre (1) mounted on a rim (5), characterized in that it comprises, in turn, a device (20; 120) for continuously measuring deformations in said tyre (1) during the travel movement of said motor vehicle, said device (20) comprising  
30 at least one first emitter (7) of a first direct light beam (8), at least

- 14 -

- one first optical sensor (9) of the luminous intensity and at least one first reflecting element (13; 113) applied to a first portion (21) of an inner surface (4) of said tyre (1), said first emitter (7) being mounted on said rim (5) and being capable of sending said first direct light beam (8) towards said first reflecting element (13; 113), said first optical sensor (9) also being mounted on said rim (5) and being capable of receiving a first reflected light beam from said first reflecting element (13; 113), measuring a prechosen physical parameter associated with said first reflected light beam and providing a first signal representing the deformation affecting the said tyre (1) along said first surface portion (21) during one revolution of said tyre (1).
- 5
- 10
9. Motor vehicle wheel according to Claim 8, characterized in that said device (20; 120) also comprises a second emitter (10) of a second direct light beam (11); a second optical sensor of the luminous intensity (12) and a second reflecting element (14) applied to a second portion (22) of said inner surface (4) of said tyre (1), situated in the vicinity of said first surface portion (21), said second emitter (10) being mounted on said rim (5) and being capable of sending said second direct light beam (11) towards said second reflecting element (14), said second optical sensor (12) also being mounted on said rim (5) and being capable of receiving a second reflected light beam from said second reflecting element (14), measuring a prechosen physical parameter associated with said second reflected light beam and providing a second signal representing the variation in distance which has occurred between said second surface portion (22) and said rim (5) during one revolution of said tyre (1).
- 15
- 20
- 25







FIG. 1




FIG. 3




FIG. 2




FIG. 5




FIG. 6

LONGITUDINAL DISPLACEMENTS during braking




FIG. 7




FIG.8

LATERAL DISPLACEMENTS during free rolling




FIG. 9

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 01/00815

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 7 B60T8/00

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B60T B60R B60C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

PAJ, WPI Data, EPO-Internal

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	FR 2 584 348 A (DERRE ANDRE) 9 January 1987 (1987-01-09) page 2, line 6 -page 3, line 7; figures 1-6	1-9
A	US 5 502 433 A (BREUER BERT ET AL) 26 March 1996 (1996-03-26) the whole document	1,8
A	DE 39 37 966 A (BREUER BERT PROF DR ING) 16 May 1991 (1991-05-16) the whole document	1,8

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents :

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

6 April 2001

Date of mailing of the international search report

12/04/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Geyer, J-L

## INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 01/00815

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
FR 2584348	A	09-01-1987	NONE	
US 5502433	A	26-03-1996	DE 4242726 A	23-06-1994
			DE 4335938 A	27-04-1995
			AT 128419 T	15-10-1995
			DE 59300682 D	02-11-1995
			EP 0602679 A	22-06-1994
			JP 6317505 A	15-11-1994
DE 3937966	A	16-05-1991	NONE	